

# Long Life Valve Regulated Stationary Battery

BATTERY MODEL	NOMINAL VOLTAGE (V)	RATED CAPACITY 25°C / 77°F(Ah)		DIMENSIONS								WEIGHT (approx.) (kg/lb)		TERMINAL EXTERNAL TYPE SHAPE	
		10HR 1.80V/CELL	1HR 1.60V/CELL	LENGTH (±2) (mm/inch)		WIDTH (±2) (mm/inch)		HEIGHT (±3) (mm/inch)		TOTAL HEIGHT (±3) (mm/inch)					
VT2100	2V	100AH	65	171	6.73	71	2.8	206	8.11	227	8.94	5.7	12.6	SCREW	A
VT2150	2V	150AH	97.5	172	6.77	102	4.02	207	8.15	227	8.94	8.50	18.70		A
VT2200	2V	200AH	130	172	6.77	111	4.37	330	12.99	356	14.02	12.60	27.58		A
VT2300	2V	300AH	195	171	6.73	151	5.94	330	12.99	356	14.02	18.50	41.0	SCREW	B
VT2400	2V	400AH	260	211	8.31	175	6.89	330	12.99	367	14.45	25.0	55.10	SCREW	C
VT2500	2V	500AH	325	243	9.57	172	6.77	331	13.03	356	14.02	30.0	66.10		C
VT2600	2V	600AH	390	302	11.89	175	6.89	331	13.03	356	14.02	36.50	80.40		C
VT2800	2V	800AH	520	410	16.14	175	6.89	330	12.99	356	14.02	50.0	110.0	BOLT&NUT	D
VT21000	2V	1000AH	650	475	18.7	175	6.89	330	12.99	356	14.02	61.50	135.0	BOLT&NUT	E
VT21500	2V	1500AH	975	401	15.79	351	13.82	342	13.46	369	14.53	92	202.60	BOLT&NUT	F
VT22000	2V	2000AH	1300	490	19.29	350	13.78	344	13.54	369	14.53	122	268.7		G
VT23000	2V	3000AH	1950	712	28.03	353	13.9	343	13.50	369	14.53	181	398.7		H

